

**DETAILED ENGINEERING DESCRIPTION AND MECHANICAL
FEATURES OF CONTINENTAL INDUSTRIE MULTISTAGE CENTRIFUGAL
BLOWER MODEL 600A**

I - BLOWER HOUSING

The centrifugal blower housing consists of an inlet head with special feature to direct air to inlet of first impeller and outlet head of special design to eliminate friction and multiple intermediate sections. These parts are made in cast iron EN-GJL-250 (ASTM A48-35B) according to rigid Continental Industrie specifications, extreme care to be exercised in assembly of interlocking cast iron EN-GJL-250 (ASTM A48-35B) intermediate sections and integral annular diffusers (baffles).

The heads are provided with integral mounting legs and rugged tie-rod lugs. The entire assembly is securely held together actually with multiple tension rods which bind the entire housing into a solid integral unit.

1.0 Inlet head

- 1.1 Flange connection DN 600, PN 10 (24")
- 1.2 Cast iron EN-GJL-250 (ASTM A48-35B)
- 1.3 Minimum wall thickness: 13 mm (0.5")
- 1.4 Can be supplied in various flange positions relative to the vertical centre line in increments of 90° (option)

2.0 Outlet head

- 2.1 Flange connection DN 500, PN 10 (20").
- 2.2 Cast iron EN-GJL-250 (ASTM A48-35B).
- 2.3 Minimum wall thickness: 13 mm (0.5")
- 2.4 Can be supplied in various flange positions relative to the vertical centre line in increments of 90° (option)
- 2.5 Has eight integrally cast reinforcing ribs surrounding the volute contour and joining up to the bearing housing mounting face for strength and to minimize vibration.
- 2.6 Has pipe connection to vent balancing piston leakage to inlet.

3.0 Intermediate section

- 3.1 Cast iron EN-GJL-250 (ASTM A48-35B).
- 3.2 Each intermediate section is cast in one piece
- 3.3 Each section has twenty two evenly spaced integrally cast ribs for increased strength. Increased surface area allows for proper heat dissipation.

Values, dimensions and reference in this brochure are approximate and intended as guide only, not for construction and are subject to change without notice



4.0 Bearing housing

The outboard bearing housings are cast iron and bolted to the outside of the head sections insuring cool operation of bearings.

- 4.1 Cast iron EN-GJL-250 (ASTM A48-35B).
- 4.2 Heat treated to relieve internal stresses and minimize distortion.
- 4.3 Two cored openings are provided to allow circulation of air (except for gas).
- 4.4 Has cast fins to improve rigidity and increase heat dissipation
- 4.5 Labyrinth type oil seal. Oil passages are generously sized to allow optimum recirculation.
- 4.6 Has air vent and magnetic plug at the bottom of the oil reservoir.
- 4.7 Provided with 4 tapped holes in the housing flange to act as bearing puller.

N.B.: When the inlet air or gas temperature is too high, we can adapt as option special bearing housings with a water or air cooling system (technical drawing on request).

5.0 Bearings

- 5.1 The rotor assembly is supported by 2 heavy duty oil lubricated ball bearings, single row, sized to withstand the thrust load also type SKF or FAG.
- 5.2 Sized for minimum 10 years of operation (Direct Drive only), following SKF L10 bearing life calculation method.
- 5.3 Bearings are mounted in outboard type bearing housings and located so that bearings may be serviced without disassembling the blower casing or piping.

6.0 Shaft

- 6.1 42CrMo4 (AISI 4140) carbon steel shaft, heat treated, straightened and stress-relieved
- 6.2 Shaft is ground all over
- 6.3 Stiff shaft design to minimize vibration
- 6.4 The diameter of the shaft end is 95 mm (3.74")

7.0 Shaft seals

- 7.1 Shaft sealing is accomplished using carbon ring seals.

8.0 Impellers

- 8.1 The impellers are fabricated in aluminium shrouds, fixed on a rigid hub in cast aluminium.
- 8.2 For minimum corrosion all aluminium alloys are non copper alloys
- 8.3 The outer diameter of the impeller is 915 mm (36")
- 8.4 Each impeller is statically balanced.
- 8.5 Impeller tip speed: 172 m/sec (562 FPS) at 3600 rpm.
- 8.6 First critical speed (6 stages) 3725 rpm.
- 8.7 Impeller assembly: to consist of a heavy steel shaft accurately machined and one or more fabricated aluminium impeller(s), statically balanced, securely keyed to shaft and held in place by lock washers and locknuts.

Values, dimensions and reference in this brochure are approximate and intended as guide only, not for construction and are subject to change without notice



9.0 Casing assembly

- 9.1 Vertically split assembly
- 9.2 Heads and sections have machined male and female joints to maintain concentricity
- 9.3 Entire casing is retained together with \varnothing 22 mm O.D.
- 9.4 Maximum allowable casing working pressure: 170 kPa (25 PSIG)
- 9.5 Joints are made gas tight with silicone sealant with following characteristics:

Viscosity	pasty mastic glue
max. space [mm]	6
Setting time	10 mn - 24 h
Shearing's resistance [DAN/cm ²]	33
Break's resistance [DAN/cm ²]	8
Max. temperature of use [°C]	-60 +260
Specific weight	1,06 at 25 °C
Hardness	35 SHA
Extension	460 %

10.0 Rotor assembly

- 10.1 Impellers, spacer are assembled on the shaft with a push to light press fit requiring little or no heat
- 10.2 Impellers, spacers are held together axially by a conventional locknut assembly
- 10.3 All impellers are keyed to shaft using a staggered key arrangement.
- 10.4 The impeller hub is fitted with a shrunk to pre-stress the bore and minimize rubbing. This also eliminates the relative thermal expansion and contraction since hubs and shaft are manufactured with different materials.
- 10.5 The rotor assembly is dynamically balanced on a computerized balancing machine

11.0 Balancing piston

- 11.1 Cast iron EN-GJL-250 (ASTM A48-35B).
- 11.2 Sized to reduce by approx. 75 % the thrust load to the outlet bearing.

12.0 Lubrication system

- 12.1 The bearing housings are oil lubricated (see detailed description in installation, use & maintenance manual).

Values, dimensions and reference in this brochure are approximate and intended as guide only, not for construction and are subject to change without notice



13.0 Recommended maximum allowable piping forces and moments on blower connections

13.1 Inlet flange

FX = 120 KG	FY = 300 Kg	FZ = 240 Kg
MX = 180 kgm	MY = 90 kgm	MZ = 90 kgm

13.2 Outlet flange

FX = 100 KG	FY = 250 Kg	FZ = 200 Kg
MX = 150 kgm	MY = 75 kgm	MZ = 75 kgm

where :

F = force

M = moment

X = Axial - parallel to rotor centre line

Y = Vertical

Z = Horizontal - normal to rotor centre line.

14.0 Vibration and noise

Vibration tolerance: 4,5 mm/s RMS

Vibration shall not exceed 4,5 mm/s RMS when measured in the vertical plane at the bearing housings with the blower operating at the design speed.

Sound level: please refer to the calculation data sheet

II - PERFORMANCES

1. All tests if required are in conformity with ASME Power Test Code.

2. For constant speed blowers:

- The head shall be within the range of 100% - 105% of the normal head at design capacity,
- The horsepower based on measured head shall not exceed 107% of the value at the specified normal operating point.

3. For variable speed machines:

- through the rotational speed, the head shall be adjusted as close as possible to the design point, with zero negative tolerance,
- the horsepower at that point shall not exceed 104% of the predicted shaft power value.

Values, dimensions and reference in this brochure are approximate and intended as guide only, not for construction and are subject to change without notice

